



LEAD 1.5 mm



Lead according to standard NF EN 12588 and DTU 40.46.



USAGE:

Back-to-back ridge beam, side edge, ridge beam, hip rafter, edge strip and gutter strip, elements of a maximum length of 1 ml.

COLOUR OF THE ADHESIVE STRIP:

Yellow.

TABLE

DIMENSIONS		WEIGHT (kg)	PACKAGING	
Length	Width mm	Nominal / Part	By pallet	
2 ml	1 000 mm	34	35 tables	PBTA0150020001000
5 ml	1 000 mm	85,5	15 tables	PBTA0150050001000
10 ml	1 000 mm	170,5	7 tables	PBTA0150100001000

FLASHING STRIP

DIMENSIONS		WEIGHT (kg)	PACKAGING	
Length	Width mm	Nominal / Part	By pallet	
10 ml	160 mm	27,5	35 strips	PBBF0150100000160
10 ml	200 mm	34	30 strips	PBBF0150100000200
10 ml	250 mm	43	30 strips	PBBF0150100000250
10 ml	300 mm	51,5	25 strips	PBBF0150100000300

FLASHING STRIP

DIMENSIONS		WEIGHT (kg)	PACKAGING	
Length	Width mm	Nominal / Part	By pallet	
5 ml	330 mm	28,5	40 strips	PBBF0150050000330

