


LEAD 2.5 mm




Lead according to standard NF EN 12588 and DTU 40.46.




USAGE:

Tile, cornice, covering, waterproofing, acroterion.



COLOUR OF THE ADHESIVE STRIP:

Black.



TABLE

DIMENSIONS		WEIGHT (kg)	PACKAGING	
Length	Width mm	Nominal / Part	By pallet	
2	1 000	57	21 tables	PBTA0250020001000
5	1 000	142	9 tables	PBTA0250050001000
10	2 200	624,5	2 tables	PBTA0250100002200

FLASHING STRIP

DIMENSIONS		WEIGHT (kg)	PACKAGING	
Length	Width mm	Nominal / Part	By pallet	
5	300	43	25 strips	PBBF0250050000300
5	330	47	25 strips	PBBF0250050000330
5	350	50	20 strips	PBBF0250050000350
5	400	57	20 strips	PBBF0250050000400
5	500	71	15 strips	PBBF0250050000500

LEAD SHEET - THICKNESS OF LEAD: 2.5 mm

DIMENSIONS		SHEETS	PACKAGING	
Length	Width mm		By pallet	
200	200		1,2	PBDE0250002000200
300	300		2,6	PBDE0250002000300
330	330		3,1	PBDE0250002000330
400	400		4,6	PBDE0250002000400
450	450		5,8	PBDE0250002000450
500	500		7,1	PBDE0250002000500



LE
PLOMB
FRANÇAIS®

Ask us for non-standard dimensions